

## Self-Adhesive products

		temp. range °C	watertight	airtight	sealing	cushioning	protecting	insulating	compatible +plexiglass	impact insulation	test certs.
<b>ZOUCHlen - polyethylene foam with closed cells, various qualities one-sided self-adhesive</b>	ZOUCHlen 110 - chemically interlaced, rigid quality, Plastazote®	-40/+70	X	X	X	X	X	X		good	
	ZOUCHlen 111 - partition wall tape, uncovered on the adhesive side	-40/+60	X	X	X	X	X	X	X	good	X
	ZOUCHlen 111G - partition wall tape, uncovered on adhesive side (flame retardant)	-40/+60	X	X	X	X	X	X	X	good	X
	ZOUCHlen 120 - reinforced by thread network (scrim)	-40/+50	X	X	X	X	X	X		good	
	ZOUCHlen 122 - partition wall tape, interlaced by radiation	-40/+60	X	X	X	X	X	X		good	
	ZOUCHlen 210 - same as ZOUCHlen 110, but higher density										
<b>ZOUCHflex - cellular rubber with closed cells various qualities one-sided self-adhesive</b>	ZOUCHflex NF 150 - pure neoprene, self-extinguishing, semi rigid: grey in colour	-40/+100	X	X	X	X	X	X		good	
	ZOUCHflex NW 152 - pure neoprene, self-extinguishing, rigid: black in colour	-40/+95	X	X	X	X	X	X		good	
	ZOUCHflex CM-L - EPDM, resistant to ozone, fine pored, soft quality	-40/+120	X	X	X	X	X	X		good	
	ZOUCHflex F 180 - natural rubber, rigid quality	-25/+80	X	X	X	X	X	X		good	
	ZOUCHflex DK - polymeric mix: neoprene+nitrile compounds: highly flame retardant	-40/+120	X	X	X	X	X	X		good	
	ZOUCHflex solar space pads - cellular rubber, with special adhesive	-40/+120						X	X		
<b>ZOUCHseal - vinyl foam one-sided self-adhesive</b>	ZOUCHseal 90 - super soft low density semi-open cell lightweight PVC Foam sealant	-30/+70	X	X	X	X	X	X		good	
	ZOUCHseal 100 - low density soft PVC Foam sealant with mostly closed cells	-30/+60	X	X	X	X	X	X		good	
	ZOUCHseal 160 - medium density closed cell PVC foam sealant	-30/+70	X	X	X	X	X	X		good	
	ZOUCHseal 200 - primarily a foam compression sealant	-30/+80	X	X	X	X	X	X		good	
	ZOUCHseal 260 - predominantly closed cell, medium hardness foam	-30/+70	X	X	X	X	X	X		good	
	ZOUCHseal 260 - predominantly closed cell, medium hardness foam										
<b>ZOUCHexpanda foam BG1</b>	polyurethane-foam sealing strip, with no chloride compounds, CFC and HCFC free	-30/+100	X	X	X	X				good	X
<b>ZOUCHmount - double-sided self-adhesive:</b>  <b>mounting tapes with varying qualities, for more information please refer to Specification Sheets</b>	ZOUCHmount 125-70	for bonding light-weight materials like hooks, trims, profiles, sign boards, emblems and other small parts									
	ZOUCHmount 125-100										
	ZOUCHmount 125 SS-100	for mounting of mirrors in bathroom and exterior applications									
	ZOUCHmount 125 SSPR-70	for indoor and outdoor applications, e.g. for the mounting of profiles and trims produced of extruded plastics									
	ZOUCHmount 125 SSPR-70 PLG1	for bonding a wide variety of permanent indoor and outdoor applications., esp. Georgian bar profiles									
	ZOUCHmount 125 PSS-70	for bonding of trims, profiles & small parts: indoor and outdoor applications as well as for mounting at low temperatures									
	ZOUCHmount 125 SA-150	offers excellent weathering & plasticizer resistance, e.g. mounting of badges, trims & mirrors in the automotive sector									
	ZOUCHmount 125 S-30	for internal & external applications which require medium load bearing properties									
	ZOUCHmount EHB	extremely powerful high performing mounting tape that offers extreme holding power in static and dynamic loads									
	ZOUCH GLAZING MOUNT 100	used as a spacer for Structural Glazing applications in combination with silicone and for conventional glazing									
ZOUCH GLAZING MOUNT 400	for mounting structural glazing systems with entire glass facades										
<b>one-sided adhesive:</b>	ZOUCHmount 125 SD-30H										
	ZOUCHmount 125 SD-70H	for mounting on difficult surfaces like polyethylene, polypropylene and polystyrene									
	ZOUCHmount 125 SD-100H										
<b>one-sided adhesive:</b>	ZOUCHmount Sekure	for mounting of externally beaded windows as a security device to prevent unauthorised removal of glass from windows									
	ZOUCH Thermomount LC	pressure sensitive mounting tape for thermal lamination on EPDM rubber profiles									
<b>ZOUCH spacer pads - special adhesive:</b>	ZOUCHcork spacer pads - natural moulded cork, grinded and bonded with adhesive				X	X					
	ZOUCHglaze spacer pads - single sided adhesive coated foam products incorporating a peelable UV stable acrylic adhesive and a high density PVC foam				X	X					
<b>ZOUCHminium:</b>	single sided high quality pure aluminium foil tape which is electrically conductive	-40/+120	X	X	X		X	X			
<b>ZOUCHlead 610:</b>	high quality pure lead foil tape for insulation and protection	-30/+120	X	X	X		X	X	X		
<b>ZOUCHcopper 620:</b>	pure electrolytic copper film, electricity conducting	-40/+120	X	X	X		X		X		