

Preliminary Product Information ZOUCH-GLAZINGMOUNT 400

Description	ZOUCH - GLAZINGMOUNT 400 is a double-sided self-adhesive polyurethane foam.
Application	The product is used as spacer for structural glazing in combination with silicone and for conventional glazing.

Product Properties (Not for specification use)		
carrier		polyurethane foam
adhesive		acrylic PSA
colour		black
liner		film, blue
density (DIN EN ISO 845)		400 kg/m ³
hardness (ASTM - D 2240)		42 shore A
force to compress 10% (DIN EN ISO 3386-1)		30 N/cm ²
thermal conductivity (DIN 52 612)		0.08 W/m K
dynamic tensile adhesion (ZOUCH test instruction 008)	at +20°C	≥ 30 N/cm ²
dynamic shear adhesion (ZOUCH test instruction 009)	at +20°C	≥ 30 N/cm ²
static shear adhesion (accord. to DIN EN 1943)	at +20°C	≥ 15 N/6,25cm ²
temperature resistance		-40°C to +80°C
weathering resistance		good
UV-resistance		good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and Shelf Live 12 month after receipt of goods, when stored at 18 °C and 60 % relative humidity out of direct sunlight, in original packaging

Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

01/2008