

Product Information ZOUCHFLEX CM-L

Description ZOUCHFLEX CM-L is a soft closed - cell foam rubber based on EPDM which is self-adhesive on one side.

Application The product is used for protecting, damping, insulating and sealing. It has very good weathering - and ozone resistance. Furthermore it is especially used, where a high chemical- and temperature resistance is required. Not recommendable is long-term contact with mineral oils and fats, nonpolar and chlorinated solvents, aromatics and strong oxidized acids.

Product Properties	
carrier	E.P.D.M sponge rubber
adhesive	solvent acrylic
colour	black
liner	silicone paper, white
density (DIN 53 420)	110 - 150 kg/m ³
compressive strength (ASTM -D 1056)	20 - 50 kPa
compression set (DIN 53 517)	at +23°C 40 - 50% at +70°C 85 - 95%
linear shrinkage 24h / 70°C / 10mm thickness	<5% at maximum
water absorption (DIN 53 428)	<5% at maximum
temperature resistance	-40°C to +120°C
environmental protection	CFC & HCFC Free
fire resistance	FMVSS 302

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

09/2008