

Product Information ZOUCMount 125 SSPR-70 PLG1

Description ZOUCMount 125 SSPR -70 PLG1 is a double-sided self-adhesive pressure-sensitive mounting tape. The tape is characterised by its outstanding initial and excellent final adhesive strength.

Application It is particularly suitable for a wide variety of permanent indoor and outdoor applications. It is especially suited for mounting of Georgian bar profiles produced of extruded plastic profiles.

Product Properties		
Carrier		polyethylene foam
Adhesive		acrylic PSA
Colour		black and white(1.0mm) white (1.6mm)
Thickness		1.0mm or 1.6mm
180° peel adhesion (according to DIN EN 1939)	at +20°C	≥16 N/25mm
shear adhesion (according to DIN EN 1943)	at +20°C at +50°C at +70°C	40 N/6,25cm ² 30 N/6,25cm ² 20 N/6,25cm ²
temperature resistance		-40°C to +100°C
Liner		Siliconised film, green
weathering resistance		good
compatibility with plexiglass		good
compatibility with mirror varnishes		good
resistance to plasticizer		good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

03/2007