

Product Information ZOUCHPRENE 36 / 65

Description ZOUCHprene 36/65 consists of a self-adhesive acrylic appropriate for a variety of different surfaces, also by high temperatures. The product is sound-absorbing and has good anti-skid qualities.

Application

- as shock-absorbing spacer device for tin sheets and plastics
- as anti-skid and vibration-dampening support pad
- as sound-absorbing and elastic bumpers

Product Properties – Not for specification purposes		
carrier	TPE	
adhesive	acrylic	
thickness	0,7 mm, 1 mm, 2 mm, 3 mm, 4 mm	
colour*	black, grey	
protective covering	silicone paper, yellow	
shore (ASTM D 2240)	30 – 40 Shore A	60 – 70 Shore A
adhesion on steel (acc. to DIN EN 1939 [AFERA 4001])	7 N/ 25 mm	9 N/25mm
shear at room temperature (acc. to DIN EN 1943 [AFERA 4012])	20 N/ 6,25cm ²	40 N/ 6,25cm ²
temperature resistance	+80°C	
Weathering resistance	2 years	
Yellowed -/colour resistance	2 years	
shear at room temperature (acc. to DIN EN 1943 [AFERA 4012])	20 N/ 6,25cm ²	40 N/ 6,25cm ²

* other colours are available on request

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Note Pressure load > 1Kp/cm² (100 kPa) should be avoided

Storage Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Forms of delivery Rolls or die-cut shapes according to customer's specification. Special surface embossing available on request.

Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

08/2008