

Preliminary Product Information ZOUCHcoll 5561 A

Description ZOUCHcoll 5561 A is a single-coated blue polyurethane tape.

Application This tape is designed for use as a tape for consumer finger plasters with high conformability as it is soft and pliable. It offers moisture vapour transmission suitable for long-term wear. The tape also has a bacterial barrier which decreases the risk of infection.

Product Properties (Not for specification use)	
carrier	blue polyurethane film
adhesive	medical acrylic adhesive
colour	white
liner	white super calendered glassine
adhesion: 90°C to Polyethylene	120 N/m (acc. to ATM-T04/095)
thickness: adhesive & carrier: liner: total:	118 micron 84 micron 202 micron (acc. to ATM-T07/010)
WVTR (37°C)	min 400 g/sqm/24h (acc. to ATM)
liner release level	1900 g/m (acc. to ATM-T13/001)

Surface preparation

It is essential, as with most pressure sensitive tapes, that the surface to which the tape is applied is clean, dry and free of grease and oil. In some circumstances in which maximum adhesion is not requested for a specific purpose, another procedure needs to be followed in consultation with Zouch Converters.

Storage and shelf-life

Two years when stored at 21°C, 50% relative humidity, out of direct sunlight, in original packaging.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Zouch Converters Ltd will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.

Address [Cumberland House, 35 Park Row, Nottingham, NG1 6EE, United Kingdom](#)
 Telephone [+44 \(0\) 1159 886295](#) Fax [+44 \(0\) 1159 886215](#)
 Email sales@zouchconverters.co.uk Website www.zouchconverters.co.uk