

Product Information ZOUCHmask 1210

Description A high-quality blue creped paper masking tape. The special adhesive provides clean removability from a wide variety of surfaces, for up to 14 days. Excellent UV resistance.

Application ZOUCHmask 1210 is designed primarily as an all-purpose product for non-critical applications within the building, painting and D.I.Y market; this tape is excellent for even the most demanding of paint application.

Product Properties (Not for specification use)	
backing	creped paper
colour	blue
total thickness	5.7mm
tensile strength	22lb/inch
elongation	6% min.
temperature resistance	short term: 100°C long term: 80°C
UV resistance 14 days	clean removal from glass

Application Apply with firm pressure to clean, non-porous surfaces. Test in an inconspicuous area before use.

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

04/2009