

## Product Information ZOUCHmask ST 65

**Description** A high-quality single-sided polyethylene tape with serrated edges for easy tearing. This product is highly conformable and flexible, offers 30 day clean removal and bonds well to glass, aluminium, plastic and wood.

**Application** ZOUCHmask ST 65 is designed primarily as an all-purpose product for outdoor masking applications, stucco and plaster masking as well as for surface protection.

Product Properties (Not for specification use)	
thickness	125 micron (+/- 10%)
colour	red
adhesion to stainless steel 90° angle	≥ 9 N/2.5cm
service temperature range	0°C to 60°C

**Application** Apply with firm pressure to clean, non-porous surfaces. Test in an inconspicuous area before use.

**Processing** The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

**Storage** Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

### Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

04/2009