

Product Information ZOUCHmount 125 – 70

Description Consists of an ordinary self-adhesive pressure sensitive mounting tape.

Application This tape serves as auxiliary mounting materials for bonding simple and light-weight material such as wall hooks, metal parts, displays as well as cardboard-boxes etc. The product must not be applied on polycarbonate and PMMA.

Product Properties – Not for specification purposes	
carrier	polyethylene foam
adhesive	acrylic dispersion
deliverable thicknesses	1.0 mm and 1.6 mm
colour	black & white: 1.0 mm white: 1.6 mm
protective covering	siliconised paper, white
shear (accord. to DIN EN 1943 / AFERA 4012)	at +20°C 15 N/ 6.25cm ² 5 N/ 6.25cm ²
adhesion (accord. to DIN EN 1939 / AFERA 4001)	breakage of foam
temperature resistance	-40°C à +60°C

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 6 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

12/2002