

Product Information ZOUCHmount 125 – SA-220

Description Consists of a double-sided self-adhesive pressure-sensitive mounting tape. This tape develops a superior final adhesive strength after 12 hours and excels by a high temperature resistance under long-term exposure.

Application It is recommendable for the mounting of badges, trims, plates made of polyvinyl chloride and metals.

Product Properties – Not for specification purposes	
carrier	polyethylene foam
adhesive	acrylic adhesive
colour	black
total thicknesses*	0.6 mm ± 0.1 mm 0.9 mm ± 0.1 mm
protective covering	siliconised paper, white siliconised/non-siliconised film, green
adhesion (accord. to DIN EN 1939 / AFERA 4001)	at +20°C ≥ 11 N/ 25 mm
shear (accord. to DIN EN 1943 / AFERA 4012)	at +20°C 50 N/ 6.25cm ² at +50°C 30 N/ 6.25cm ² at +70°C 20 N/ 6.25cm ² at +100°C 10 N/ 6.25cm ²
temperature resistance	- 40°C to + 90°C at short term: up to +100°C
weathering resistance	very good
resistance to (salt) water, weak acids and alkaline liquors and fungal attacks	good
compatibility with plexiglass	good
resistance to softening agents	good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 6 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

04/2003