

Product Information ZOUCHmount 125 SD - 100 H

Description ZOUCHmount 125 SD-100H is a double-sided self-adhesive pressure-sensitive mounting tape.

Application This multifunctional tape excels by its paramount initial and final adhesive strength. It is appropriate for the permanent mounting of small parts such as wall hooks, displays and holding devices. It is in particular appropriate for the adhesion of critical plastic materials as, for example, polyethylene, polypropylene and polystyrene.

Product Properties – Not for specification purposes	
carrier	polyethylene foam
adhesive	synthetic rubber
deliverable thickness	0.8 mm
colour	white
liner	siliconised paper, white
shear (accord. to DIN EN 1943 / AFERA 4012)	at +20°C 60 N/6.25cm ²
tear-off resistance (adhesion) (T-block) (accord. to Ford Standard)	at +20°C 35 N/ cm ²
temperature resistance	-40°C to +70°C
resistance to (salt) water, weak acids and alkaline liquors and fungal attacks	good
compatibility with plexiglass	good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 6 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

01/2007