

Product Information ZOUCHmount 125 SD - 100 H

Description ZOUCHmount 125 SD-100H is a double-sided self-adhesive pressure-sensitive mounting tape.

Application This multifunctional tape excels by its paramount initial and final adhesive strength. It is appropriate for the permanent mounting of small parts such as wall hooks, displays and holding devices. It is in particular appropriate for the adhesion of critical plastic materials as, for example, polyethylene, polypropylene and polystyrene.

Product Properties – Not for specification purposes		
carrier		polyethylene foam
adhesive		synthetic rubber
deliverable thickness		0.8 mm
colour		white
liner		siliconised paper, white
180° peel adhesion (accord. to DIN EN 1939)	at +20°C	≥ 11 N/25mm
shear adhesion (accord. to DIN EN 1943)	at +20°C	35 N/ 6.25cm ²
	at +50°C	20 N/ 6.25cm ²
	at +70°C	15 N/ 6.25cm ²
temperature resistance		-40°C to +70°C
weathering resistance		good
compatibility with plexiglass		good
compatibility with mirror varnishes		good
resistance to plasticizer		good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 6 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

08/2008