

## Product Information Zouchlead 610

**Description** Consists of a one-side self-adhesive film of pure lead.

**Application** This product serves as insulation and protection. It excels with a good adhesive power on even surfaces, is waterproof and airtight. Electrically conductive and used as a contact maker and also in shielding appliances

Product Properties – Not for specification purposes	
carrier	film of pure lead
adhesive	acrylate adhesive
thickness	0.10 mm
protective covering	siliconised film
adhesion at +20°C (correspond. to DIN EN 1939 / AFERA 4001)	20 N/25mm
shear at +20°C (correspond. to DIN EN 1943 / AFERA 4012)	30 N/6.25cm <sup>2</sup>
temperature resistance	-30°C to +120°C

**Format** Supplied as sheets, rolls, die-cut shapes or pads

**Processing** The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

**Storage** Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

### Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

05/2007