

Product Information Zouchlen 122

Description Consists of a one-side self-adhesive, closed-cell ethylene vinyl acetate foam, reinforced by a scrim.

Application The product is used for sealing and sound absorption and serves as protection and insulation.

Product Properties – Not for specification purposes		
carrier		ethylene vinyl acetate foam (E.V.A)
adhesive		acrylic dispersion
colour		grey and white
protective covering		siliconised film, white
density (DIN 53 420)		25 kg/m ³
compressive strength (ISO 3386/1)	at 20% 50%	30 kPa 90 kPa
compression set (DIN 53 517)	at +23°C	60%
water absorption (DIN 53 428)		1% max.
thermal conductivity (ISO 8302)	at +10°C	0.038 W/mK
temperature resistance		-40°C to +60°C

Format Supplied as sheets, rolls, die-cut shapes or pads

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage Unprocessed in the original cardboard box, 12 months after receipt by the customer, at a relative atmospheric humidity of about 60% and a temperature of 18°C.

Special Information

All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

03/2007