

Product Information Zouchseal 100 “The Quick Roll”

Description ZOUCHSEAL 100 is a single coated self-adhesive PVC foam sealant in a mostly closed-cell structure.
The tape is delivered in rolls. After unwinding the roll you will get exposed adhesive with the release liner left on the foam to prevent stretch.

Application The product is appropriate for all kinds of indoor and outdoor sealing applications. It is characterised by good sealing properties against water, air, sound, heat and cold.

Product Properties (Not for specification use)	
carrier	polyvinyl chloride foam
adhesive	modified acrylic PSA
colour	black (other colours available subject to M.O.Q.)
liner	siliconised paper, brown
density (DIN 53 420)	100 – 125 kg/m ³
compressive strength (ASTM 1667)	0 sec. 12 - 33 kPa 60 sec. 4 - 16 kPa
compression set (DIN 53 572)	≤ 45%
water absorption	≤ 30%
flame resistance (FMVSS 302)	≤ 100 mm/min. (6 mm)
waterproofness (U test)	30% compression
temperature resistance	-30°C to +60°C

Format Supplied as sheets, rolls, die-cut shapes or pads

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and Shelf Live 12 months after receipt of goods, when stored at 18 °C and 60 % relative humidity out of direct sunlight, in original packaging

Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

02/200 8